



Model AR8-Tank

- Electric: 8.0 KW/240 Volts
- Steam Output: 28 LBS (12.7 KG)/Hour* (on 240V)
- Pressure Range: 5 to 85 PSIG (.3 to 5.8 bar)
- Dimensions: 17" x 15" x 35" high (43 x 38 x 89 cm)
- Shipping Weight: 130 LBS (60 KG)
- Safety Valve Setting: 100 PSIG (6.8 bar)
- Automatic water level control
- High pressure pump water feed
- Five gallon (19 liter) storage tank
- Portable & mounted on wheels
- Gauge glass safety shield provided
- Cool plastic handles on all valves
- Manual blowdown valve
- Positive low water shut off
- Supports four (4) electric steam irons
- Thermostatically controlled
- Ships via U.P.S.
- Built in accordance with requirements of the ASME boiler and pressure vessel code
- Bears the National Board of Boiler & PV inspectors stamp
- U.L. listed (CSA/CRN for Canada)

Also Available

JR-TANK 1.5 KW/240V
 AR4-TANK 3 KW/240V
 AR6-TANK 6 KW/240V



R - RH - RHC Series

- Electric: 7.5 KW thru 120 KW
 208, 240, 480, 600 Volts
 1 Phase (7.5 KW-36KW)
 3 Phase (7.5 KW-120 KW)
- Steam Output: 26 to 418 LBS/Hour*
 (12 to 189 KG/Hour*)
- Pressure Range: 5 to 85 PSIG (.3 to 5.8 bar)
- Safety Valve Setting: 100 PSIG (6.8 bar)
- Automatic water level control
- R=Solenoid valve water feed
- RH=Pump water feed with solenoid valve
- RHC=Condensate return tank with pump
- Gauge glass safety shield provided
- Manual blowdown valves
- Low water control
- Supports (4) to (48) electric steam irons
- Pressure controlled
- Manual reset hi-limit pressure control
- Built in accordance with requirements of the ASME boiler and pressure vessel code
- Bears the National Board of Boiler & PV inspectors stamp
- U.L. listed (CSA/CRN for Canada)

*LBS (KG)/Hour Steam from and at 212° F.

SEICKEL & SONS INC.

MANUFACTURERS & REBUILDERS OF STEAM PRESSING EQUIPMENT

360 ELIZABETH AVE., NEWARK, NJ 07112 TEL.973-242-1948 FAX 973-733-4956
 315 WEST 36TH ST., SUITE 504, NY, NY 10018 TEL.212-290-2120 FAX 212-290-2140
 TOLL FREE IN U.S. 1-800-338-5044

WEB WWW.SEICKEL.COM

SALES@SEICKEL.COM